

ARACO Release Agent

Powdered release agent for stamped concrete

Product Description

ARACO RELEASE AGENT is a premixed special hydrophobic releasing powder mixed with high quality pigments

Applications

ARACO RELEASE AGENT is suitable to be use as a release agent for stamped concrete in:

- Parking areas
- Warehouses
- Side walks
- Garden landscaping

Product Advantages

- Water resistant
- Prevents stamping mould from sticking to concrete surfaces

Limitations


- The substrate must be free from any surface water
- Uneven application on can lead to uneven color patterns on the finished stamped concrete.
- Do not leave excess of **ARACO RELEASE AGENT** adhering to the concrete as this may affect the adhesion of the sealer.

Characteristics

Color	Available in a range of color
Storage condition	Store in a dry area between 5C and 35C. Protect from direct sunlight
Shelf Life	12 months minimum from production date if stored properly in original unopened packaging.

Safety Instructions

The product may cause skin irritation. Wear gloves and goggles and apply barrier cream to your hands. In contact with eyes or mucous membrane. flush immediately with plenty of warm water and seek medical attention without delay.



Package: 10 Kg bag

Consumption: 5-7 kg/m²

Product Application

Before using **ARACO RELEASE AGENT**, Apply the concrete floor hardener **ARACO TOPCRETE** and eliminate any float marks of the hardener using a steel trowel. The surface should be well trowelled to achieve a final finish.

Prior to imprinting, the trowelled slab should be covered with **ARACO RELEASE AGENT** at a rate of 5 - 7 m² /kg. The crew should be equipped with a minimum of 6 or more mats and a floppy. Start setting a reference line then placing the first mats using this line and move across the slab.

When stamping, the mats should be tamped using a special pounder without delay. The finished slab should be left for a minimum of 2 - 3 days to set.

All excess of **ARACO RELEASE AGENT** should be brushed off and then cleaned using pressurized water. The slab must be completely dry before the sealer coat is applied

Legal Notes

The information, recommendations, and application are based on ARACO current knowledge and experience of the products when properly stored, handled, and applied under normal conditions. ARACO products are guaranteed against defective materials and manufacture and sold subject to standard conditions. Users should always refer to the most recent technical data sheet for the product concerned, copies of which will be supplied on request.